



Voyager EMM

Fueled by Cistech Solutions technology, VoyagerEMM is an integrated Radio over IP (RoIP) system with interfaces for radio, Ethernet and handset audio. With ultra-low power requirements, VoyagerEMM is ideal for battery powered applications where SWaP is critical.

VoyagerEMM provides four E&M radio interfaces for connection of audio for push-to-talk (PTT) radios. Three Ethernet ports are also available along with a handset/headset/speaker connector for handsets such as the military H-250.

The VoyagerEMM is designed for use in austere environments and is housed in a ruggedized chassis with dust caps on all ports.



Portable



Rugged



Low Power

COMMUNICATE MORE, CARRY LESS

KLAS

Specifications

Physical Specifications

- 188 x 145.2 x 26mm (W x L x H)
- Weight: 900g

Electrical Specifications

- 12 – 28 VDC Input for operation
- Power consumption: < 3 Watts

Construction

- Integrated aluminum chassis

Operating Temperature

- -25°C to 60°C

System Management

- Central or Local Management
 - Web
 - Telnet (Base Configuration) Serial (Base Configuration)

IP Configuration

- IP Address allocation Static/ Dynamic
- Network Monitoring Support SNMP V2
- Network Time Protocol Support SNTP
- Adjustable MTU Support (VPN)

CODECs Including

- G.711, G729, ILBC, Speex, SILK, OPUS, AMR
- Dynamic Payload Selection

Compliance

- Designed to meet:
 - MIL-STD-810G
 - MIL-STD-461 E
 - FCC Part 15B

Ports

- 2 x Ethernet RJ-45 on front
- 1 x Ethernet Mill-Max on rear
- 1 x Console RJ-45 Management port
- 4 x E&M RJ-45 radio ports
- 1 x H-250 Handset connector

LMR Port

- 4 Wire E&M 600 Ohm
- Half / Full Duplex
- Radio PTT Trigger Options:
 - Packet / Voice
- PTT Signal Support (Optically Coupled) Relay
 - Isolated (Close Circuit)
- COR Signal Support (Optically Coupled)
 - Close Circuit
 - DC Switched
 - VAD
- Audio Level Management
 - AGC
 - Configurable input gain (dB)
 - Configurable output gain (dB)
- Audio Input Range (Transformer Coupled)
 - -60 to +0 dBm (600 Ohm)
- Audio Output Range (Transformer Coupled)
 - -60 to +0 dBm (600 Ohm)
- SIP Channel Connection Options
 - Call on load
 - Call on activity

Handset port (H-250)

- H-250 Handset Support
- PTT
- Sidetone
- Volume Controls
- TalkGroup Selection
- Switched DC handset output power on pin F

Indicators

- Handset PTT
- Network Activity
- Radio Port PTT/COR
- Blackout Mode

IP RTP Channel Options

- RTP Channel Support
 - Multicast
 - Unicast (RTP/SRTP)
 - SIP (Secure / Non Secure)
- RTP Channel Options
 - QoS
 - Codec
 - RTP Payload Size

E&M

- Frequency response selectable for 300 Hz to 3.4 KHz
- Tx Audio
- Rx Audio
- Press to Talk (PTT)
- Squelch (SQL)

Key Features

- Four RJ-45 radio ports supporting Press to Talk (PTT) and Squelch (SQL) functions
- Low power consumption
- Data and power backplane to simplify cabling
- Lightweight aluminum construction
- Two Ethernet ports on the front panel and one on the rear panel
- Support for a handset/headset/speaker such as the H-250
- Toggle switch allows switching between radio 1–4 and adjusting the volume level.



Voyager EMm Front View



Voyager EMm Rear View